



Rec'd PET/PTO 20 JAN 2005



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

10/521919
(10) International Publication Number
WO 2004/008970 A1

(51) International Patent Classification: A61B 6/12

(21) International Application Number:
PCT/GB2003/003261

(22) International Filing Date: 21 July 2003 (21.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0216893.8 20 July 2002 (20.07.2002) GB

(71) Applicant (*for all designated States except US*): THE
UNIVERSITY OF SURREY [GB/GB]; Guildford,
Surrey GU2 7XH (GB).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): MORTON, Edward,
James [GB/GB]; 37 Banders Rise, Merrow, Guildford,
Surrey GU1 2SL (GB).

(74) Agent: BUTLER, Lance; Barker Brettell, 10-12 Priests
Bridge, London SW15 5JE (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMAGE COLOURING



(57) Abstract: In a method of fluoroscopic X-ray imaging employing an X-ray irradiation unit, image processor and an imaging chain including a display monitor, the key parameters of a displayed greyscale image are highlighted by the addition of colouring according to a predetermined colour coding pattern.

BEST AVAILABLE COPY

WO 2004/008970 A1

Image Colouring

This invention relates to applying colour to an image. It is particularly concerned with the addition of colour to images employed in X-ray fluoroscopy.

- 5 X-ray fluoroscopy is a commonly used procedure for guiding interventional procedures within the body, or for visualising the structure/function of internal organs in the body. It is characterised by the use of X-ray imaging at video rate (normally 6 to 30 frames per second).
- 10 Conventionally, an X-ray imaging system for fluoroscopy comprises an X-ray irradiation unit (for example an X-ray tube and generator, collimator assembly, beam filter(s) and light beam diaphragm) combined with an imaging chain (for example, an X-ray image intensifier, lens system with optical iris, video camera, image processor and monitors).
- 15 The images are observed by one or more specialist clinicians. The monitors have hitherto been greyscale units, giving an image which relies on clear contrast between the displayed features to permit the clinicians to assess the progress of the respective procedure.

- Typical clinical applications of fluoroscopy include interventional
- 20 neuroradiology, cardiology and peripheral vascular angiography. These are all techniques involving a high degree of risk of harm to a patient and thus require extremely careful control of instruments such as catheters to be inserted into the patient. In particular it is highly desirable that the X-ray images presented to clinicians operating the applications should be
- 25 very clear in indicating the detail of the part of the body under investigation and in showing the precise location of inserted instruments.

A related problem is that prolonged exposure to X-ray irradiation poses in itself a health risk, especially to the patient undergoing treatment, but

also to the clinicians conducting the treatment. Although the dose received by the clinicians at an individual treatment may be relatively small, their repeated exposure in treatment of successive patients adds to a total level of irradiation which places an upper limit on the number of treatments they can conduct. It is therefore desirable that the period of exposure to irradiation should be kept as short as possible, which in turn requires that clinicians shall be quickly able to assess an image and the action they need to take in response to it.

During interventional procedures in which X-ray fluoroscopy or angiography is used to guide the clinician, important details such as the tip of a catheter may become obscured. This is particularly the case when the catheter passes up a vessel that lies parallel to the X-ray beam direction. A further example occurs when the catheter tip is obscured by the presence of a bolus of contrast agent as it passes from the catheter into the vessel. Since the clinician frequently wishes to identify the location of the catheter tip with respect to patient soft-tissue anatomy, such obscuring of the tip is most unhelpful. Indeed, this is an instant when in many cases a full knowledge of the catheter tip position relative to the patient anatomy is most critical.

Our co-pending patent application on image control, filed on even date with the present application, relates to the use of a combination of parameters derived from the image to calculate output signals to enhance control of the process. An important preferred feature of that application is the use of computer-based algorithms to enhance the image quality and thus control of the procedure in question.

The present invention can similarly benefit from the associated use of control algorithms. It is moreover possible to partition the algorithms to apply colour for use with parallel computing systems.

The present invention has the objective of improving the quality of image presented to clinicians so as to facilitate their rapid perception of the important features of a fluoroscopic image or image sequence.

5 According to the invention there is provided a method for fluoroscopic X-ray imaging employing an X-ray irradiation unit, image processor and an imaging chain including a display monitor, characterised in that key parameters of a displayed greyscale image are highlighted by the addition of colouring according to a predetermined colour coding pattern.

10 The invention is based on the high level of sensitivity of the human eye to colour. The use of colour as claimed herein for X-ray fluoroscopy to substantially aids clinicians' perception of information in image sequences. Their enhanced perception has the great advantage of permitting reduction of procedure times, therefore reducing the irradiation dose received by the patient.

15 Therefore, the first example of the use of colour is to colour the catheter tip with respect to the greyscale displayed X-ray image.

In a particularly advantageous embodiment of the present invention the position of a catheter tip in the displayed image is tracked using suitable algorithms. Thus even when the catheter tip is momentarily obscured
20 from the camera, the image presented to the clinicians still gives a reasonably accurate indication of the tip's position.

A predetermined colour coding pattern for the highlighted features is of particular importance. It ensures that a clinician familiar with the coding pattern can instantly recognise a highlighted item, its position on the display, and thus in the body, and its rate and direction of movement
25 across the screen and within the body. The preferred colours according to the invention are described below with reference to the respective items of equipment, procedure and anatomical details.

The highlighted parameters are preferably displayed as at least normal size. A larger than normal display can be employed for one or more of the parameters if the observer conditions require this.

5 In the preferred colour coding according to the invention the colour for the catheter tip is light green. Typically, the colour is applied in a regular shape (i.e. a disk) rather than an irregular shape (such as might be recorded in the actual image), again to aid clinician perception.

10 In a further example, the catheter may include orientation markers which are normally small attenuating beads placed along the catheter wire. In this case, the orientation markers are preferably coloured in alternate colours (cyan and yellow are most preferred) to aid a three-dimensional perception of catheter position.

15 In a further example, the path followed by the catheter tip may be displayed by a "tail" of variable persistence. Normally, such a tail would be displayed in a single colour (dark green is preferred), but variable shaded tails may be used to encode velocity information as well as position. In this case, the colour of the tail can vary from dark green (slow velocity) to bright green (high velocity). Alternatively a variable colour scale can be used such as a hot-wire scale (red-orange-yellow-white).
20 Normally, the persistence of the tail is several seconds, although it can vary from zero to infinite duration. Markers at the end of the tail are preferably displayed at low intensity (almost transparent), while those at the head of the tail are high intensity (almost opaque). In a further option, the colour of all elements in the tail can be made the same, and
25 they are merely removed from the end of the tail at the required persistence lifetime.

In a further embodiment of the invention, the catheter wire may be identified and coloured (e.g. in dark red) to allow the clinician to observe motion of the full catheter wire within the patient. This can help to

identify any coiling of the catheter before it becomes problematic, and can also aid clinician perception on how best to manipulate the catheter through the vessel.

5 In a further embodiment, colour can be used to indicate the relative movement of features. For example, a contrast agent flowing upwards can be coloured red while a contrast agent moving downwards can be coloured blue. This aids three-dimensional perception of the contrast flow and hence of patient anatomy.

10 In a further example, colour may be used to indicate the presence and/or velocity of contrast agent as it flows through vessels. For example, a binary segmented image of vessels containing contrast agent can be generated, and then the segmented regions (i.e. the blood vessels) coloured to indicate velocity of the contrast. Typically a rainbow spectrum (red-orange-yellow-green-blue-violet) can be used with the
15 coloured image overlaying the greyscale anatomical image. In this case red represents high velocity and violet low velocity. Further, the intensity of the colour may be related to the remaining intensity of contrast in the vessel, such that the colour image fades as the contrast agent disperses. Alternatively, the coloured vessels may be maintained
20 on the display, and the live catheter tracked through the coloured image. In this case, the catheter tip colour needs to be adjusted to contrast with the vessel colour.

Moreover the location and motion of the patient's anatomical features (e.g. regions of cardiac tissue) can be colour coded to aid clinician
25 diagnosis. This is particularly important during slow motion playback of recorded image sequences to aid clinician diagnosis.

The applied colours to a greyscale anatomical image may be transparent or opaque.

A method for generating suitable colouring based on information extracted from the image itself is required. The preferred system for generating this information comprises an image computer that connects the image sensor to the image display. The image computer interprets the input image by calculating a set of low-level image parameters. Examples of the parameters include pixel-by-pixel motion vectors, pixel-by-pixel statistical properties such as significance of change in grey level and location of image features such as the catheter tip, orientation markers and guide wire. Based on the extracted data, high level parameters are determined such as global patient motion and the location and velocity of contrast agent.

Low level and high level parameters are then combined to determine suitable colouring for the displayed image. This is achieved by applying algorithms which use linear rule-based logic, fuzzy logic, neural networks and/or other linear or non-linear methods as appropriate.

Typically, the image computer comprises a parallel set of processors (e.g. digital signal processors or PCs) connected through a high speed digital backplane or via a high bandwidth network. Alternately, a custom processor may be designed, and construction techniques including high density three-dimensional interconnects and multi-chip modules may be employed. Often, programmable logic devices can be used to speed up otherwise compute intensive tasks such as binary segmentation of images.

There are several ways to segment the image data amongst the various processors. Typically, in a bespoke system containing embedded processors, complete images are copied to all processors simultaneously, and each processor determines the value of a single parameter or set of parameters. The results are fed back to further processors that implement the decision making algorithm and apply the colours into the output image frame buffer. In a commodity PC network (e.g. a beowolf PC cluster) it

is generally more efficient to send part of an image to each PC in the cluster, and perform all processing on that segment of the image within the same PC. Generally, multi-processor PCs are required, with one or more processors to extract the basic information, and one to generate the output image colours.

The present invention is further described with reference to the accompanying figure, which is a diagrammatic view of a cerebral blood vessel with an interventional catheter in position.

The blood vessel, indicated by the reference numeral 10, has an associated aneurism 12 which the clinician seeks to address. A catheter which has been inserted into the vessel 10 has its tip identified by a circular marker disc 14. The catheter has within it a wire 16 with a coil memory. When the catheter tip 14 reaches the part of the aneurism 12 the clinician wishes to treat the wire 16 is pushed out of the end of the catheter and reverts within the vessel 10 to its coiled shape and provides an obstruction around which blood clotting can occur, thereby restricting the blood flow and relieving pressure on the aneurism 12.

Using the preferred colour coding of the invention the display image, which is otherwise greyscale, shows the catheter tip 10 as substantially opaque light green and the catheter wire as substantially opaque dark red. A tail showing the previous movement of the tip 10, which substantially follows the line of the wire 16 is opaque dark green at the tip end and transparent dark green remote from the tip.

Claims

1. A method for fluoroscopic X-ray imaging employing an X-ray irradiation unit, image processor and an imaging chain including a display monitor, characterised in that key parameters of a displayed greyscale image are highlighted by the addition of colouring according to a predetermined colour coding pattern.
5
2. A method as claimed in claim 1, in which the position of a catheter tip in the displayed image is highlighted in colour.
3. A method as claimed in claim 1 or claim 2, in which the position of a catheter tip in the displayed image is tracked using suitable algorithms.
10
4. A method as claimed in any preceding claim, in which the highlighted features are coloured according to predetermined colour coding pattern.
5. A method as claimed in any preceding claim, in which the highlighted parameters are preferably displayed as at least normal size.
15
6. A method as claimed in any preceding claim, in which the colour for the catheter tip is light green.
7. A method as claimed in any preceding claim, in which the colour is applied in a regular shape.
- 20 8. A method as claimed in any preceding claim, in which orientation markers are placed along a catheter wire.
9. A method as claimed in claim 8, in which the orientation markers are small attenuating beads.

10. A method as claimed in claim 8 or claim 9, in which the orientation markers are of alternate colours.

11. A method as claimed in claim 10, in which the alternate colours are cyan and yellow.

5 12. A method as claimed in any preceding claim, in which the path followed by a catheter tip may be displayed by a "tail" of variable persistence.

13. A method as claimed in claim 12, in which the tail is displayed in a single colour.

10 14. A method as claimed in claim 13, in which the tail colour is dark green.

15. A method as claimed in any preceding claim, in which the tail is displayed in a variable shade.

15 16. A method as claimed in claim 15, in which the tail colour varies from dark green to bright green.

17. A method as claimed in any of claims 12 to 16, in which the displayed persistence of the tail is several seconds.

18. A method as claimed in any of claims 12 to 17, in which markers at the end of the tail are displayed at low, almost transparent, intensity
20 while those at the head of the tail are of high almost opaque intensity.

19. A method as claimed in any of claims 12 to 14, in which the colour of all elements in the tail is the same.

20. A method as claimed in any preceding claim, in which a catheter wire is identified and coloured.

21. A method as claimed in claim 20, in which the wire is coloured dark red.

22. A method as claimed in any preceding claim, in which colour is used to indicate the relative movement of features.

5 24. A method as claimed in any preceding claim, in which colour is used to indicate the presence and/or velocity of contrast agent.

25. A method as claimed in claim 24, in which a rainbow spectrum (red-orange-yellow-green-blue-violet) is used for the coloured image to overlay the greyscale anatomical image.

10 27. A method as claimed in claim 25, in which red represents high velocity flow and violet low velocity flow.

28. A method as claimed in any one of claims 24 to 27, in which the intensity of the colour is related to the remaining intensity of contrast in a blood vessel.

15 29. A method as claimed in any preceding claim, in which the location and motion of the patient's anatomical features are colour coded.


30. A method as claimed in any preceding claim, in which the colours to a greyscale anatomical image are transparent or opaque.

20 31. A method as claimed in any preceding claim, in which the colouring is generated from information extracted from the image itself.

32. A method as claimed in claim 31, in which the information comprises an image computer that connects an image sensor to the image display.

33. A method as claimed in any preceding claim, in which low level and high level parameters are combined to determine suitable colouring for the displayed image.
34. A method as claimed in any preceding claim, in which an image
5 computer comprises a parallel set of processors (e.g. digital signal processors or PCs) connected through a high speed digital backplane or via a high bandwidth network.
35. A method as claimed in any one of claims 1 to 34, in which an
10 image computer is a custom processor employing high density three-dimensional interconnects and multi-chip modules.
36. A method as claimed in any preceding claim, in which image data is segmented among image processors in a bespoke system in which complete images are copied to all processors simultaneously.
37. A method as claimed in any preceding claim, in which a separate
15 processor determines the value of a single parameter or set of parameters and the results are fed back to further processors that implement a decision making algorithm to apply colours to the image.

1/1



INTERNATIONAL SEARCH REPORT

International Application No.

PC. B 03/03261

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B6/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 092 391 A (GEN ELECTRIC) 18 April 2001 (2001-04-18) paragraph '0028! - paragraph '0036! column 10, line 10 - line 48	1-7, 20-32
X	EP 0 518 282 A (TOKYO SHIBAURA ELECTRIC CO) 16 December 1992 (1992-12-16) column 10, line 18 -column 13, line 35	1-7, 30-33
X	WO 00 28472 A (HIGMAN RYAN D ;HIVOLTZE JIMENEZ ALEXANDER (US)) 18 May 2000 (2000-05-18) page 10, line 11 -page 11, line 18	1,29-33
X	EP 0 587 334 A (PICKER INT INC) 16 March 1994 (1994-03-16) page 9, line 5 - line 26	1,24-28
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

21 October 2003

Date of mailing of the international search report

28/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Manschot, J

INTERNATIONAL SEARCH REPORT

Inter. al. Application No.

PC. 03/03261

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 87136 A (VISUALIZATION TECHNOLOGY) 22 November 2001 (2001-11-22) page 9, line 25 -page 10, line 12 page 13, line 25 -page 14, line 14 page 19, line 17 -page 20, line 8 -----	1,2,8-11
A	WO 02 36013 A (EVRON RAMI ;PAIEON INC (US)) 10 May 2002 (2002-05-10) page 9, line 2 -page 10, line 10 -----	8,9

INTERNATIONAL SEARCH REPORT

Int. Application No

PC 3 03/03261

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1092391	A	18-04-2001	US 6463121 B1 EP 1092391 A1 JP 2001149356 A	08-10-2002 18-04-2001 05-06-2001
EP 0518282	A	16-12-1992	JP 4364677 A DE 69211057 D1 DE 69211057 T2 EP 0518282 A1 US 5285786 A	17-12-1992 04-07-1996 23-01-1997 16-12-1992 15-02-1994
WO 0028472	A	18-05-2000	AU 1714200 A WO 0028472 A1	29-05-2000 18-05-2000
EP 0587334	A	16-03-1994	DE 69325485 D1 DE 69325485 T2 EP 0587334 A2 JP 6205771 A US 5396418 A US 5485493 A US 5544212 A	05-08-1999 28-10-1999 16-03-1994 26-07-1994 07-03-1995 16-01-1996 06-08-1996
WO 0187136	A	22-11-2001	US 6484049 B1 US 6490475 B1 AU 5738401 A CA 2407616 A1 EP 1278458 A2 WO 0187136 A2 US 2003130576 A1 US 2003088179 A1	19-11-2002 03-12-2002 26-11-2001 22-11-2001 29-01-2003 22-11-2001 10-07-2003 08-05-2003
WO 0236013	A	10-05-2002	AU 1263902 A EP 1341443 A1 WO 0236013 A1	15-05-2002 10-09-2003 10-05-2002

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.